

Amplifier

Audio, Mains Powered



LB0081-101 240V.AC. 50/60Hz

Description:

The IEC mains operated amplifier LB0081-001 is a general purpose audio amplifier and is fitted with a speaker suitable for the classroom. It is complete with both a mains power ON/OFF switch and a speaker ON/OFF switch.

Input signal can be via a 3.5mm diameter phone jack (low level signal) or via standard 4mm sockets (higher level signal). When the phone jack is used from a microphone or other signal source, the maximum input signal should not exceed 20mV or distortion will occur. When the 4mm sockets are used, signal levels up to 200mV can be applied.

The speaker can be switched on and off from the front panel. Two 4mm sockets are provided for an oscilloscope output so that the signal wave form can be studied. When an oscilloscope is used to view the waveforms, the speaker switch should be off to avoid waveform distortion due to the inductance of the speaker.

Specifications:

- Inputs:** 3.5mm phone jack: 20mV max.signal 4mm sockets: 200mV max.signal.
- Outputs:** Inbuilt loud speaker with ON/OFF switch. 4mm sockets for connection to external speaker or oscilloscope.
- Power:** 500mW max.output power.

Length: 180mm	Width: 170mm	Height: 85mm	Weight: 1.1kg
---------------	--------------	--------------	---------------

Designed and manufactured in Australia

INDUSTRIAL EQUIPMENT & CONTROL PTY.LTD.

61-65 McClure St. Thornbury. 3071 Melbourne. Australia
 Tel: 61 (0)3 9497 2555 Fax: 61 (0)3 9497 2166 www.iecpl.com.au